



Unless otherwise specified
 1. Dimensions are in inches
 2. Cut cable & Cable assembly length tolerance is $\pm .125$
 3. Machined tolerances are:
 .XX $\pm .01$.XXX $\pm .005$ Angles 1
 4. Break all edges .005 min
 5. Finish 63 micro inches
 6. Dimensions apply after finish
 7. Concentricity = .025 TIR

DRAWN BY RDK REV

CHECKED BY

PROPRIETARY AND CONFIDENTIAL

This drawing and these specifications are the exclusive property of GRIPLOCK SYSTEMS LLC, and shall not be divulged, reproduced, copied, or used as the basis for the manufacture or sale of apparatus without the express written authorization of GRIPLOCK SYSTEMS LLC.

REF: DATE: 08/07/15

MATERIAL: VARIOUS

SCALE: 1:1 FILE: ZF-15-38IP-KFT-R-S

**GRIP
LOCK**
SYSTEMS

GRIPLOCK SYSTEMS

793 Duncan Reidville Rd. Duncan, SC 29334
 Phone (805) 566-0064 Fax (805) 566-0065

PART NUMBER: ZF-15-38IP-KFT-R-S

DESCRIPTION:
 3/8" IPS GRIPPER FOR 3/64" &
 1/16" 7X7 OR 7X19 CABLE