



DG-15Z-TC-300-SAT

Each suspension has a safe working load of 60lbs, two suspension points 120lbs.

Unless otherwise specified  
 1. Dimensions are in inches  
 2. Tolerances are:  
 .XX ±.01 .XXX ±.005 Angles 1°  
 3. Break all edges .005 min  
 4. Finish 63 micro inches  
 5. Dimensions apply after finish  
 6. Concentricity = .025 TIR

DRAWN BY: \_\_\_\_\_ REV: \_\_\_\_\_  
 CHECKED BY: \_\_\_\_\_

**PROPRIETARY AND CONFIDENTIAL**

This drawing and these specifications are the exclusive property of GRIPLOCK SYSTEMS LLC and shall not be divulged, reproduced, copied, or used as the basis for the manufacture or sale of apparatus without the express written authorization of GRIPLOCK SYSTEMS LLC.

REF: \_\_\_\_\_ DATE: \_\_\_\_\_  
 MATERIAL: \_\_\_\_\_  
 SCALE: 1:5 FILE: Panel Multi Options Update2



**GRIPLOCK SYSTEMS**

1132 Mark Ave., Carpinteria, CA 93013  
 Phone (805) 566-0064 Fax (805) 566-0065

GRIPLOCK P/N: GI-AS16-44-TC

DESCRIPTION:  
 Panel Hanging System